

ALT550R RECESSED IP65 LED WALL LIGHT

ALT550R is a commercial wall light luminaire ideally suited to commercial projects, common areas, corridors and stairway lighting. The fitting features integral constant current LED driver and robust construction with corrosion resistant powdercoat surface treatment. ALT550 is also available in a surface mount version (ALT550S).

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	18W
LED Driver Classification:	Integral LG-D LED Driver
Light Source Classification:	Citizen SMD LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Nominal Dimensions:	230x196mm
Construction Material:	Cast Aluminium, Powdercoated
Standard Colour/Finish:	Dark Grey
Recommended Ambient Temp:	-10 ~ +50°C

**CONFIGURATION OPTIONS**

- Surface mounted version also available (ALT550S)
- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	85lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	60° / Indirect Visor

**CONTROL OPTIONS**


This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**CASAMBI****COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	ALT550R
Specify LED CCT:	3000K / 4000K / 6000K
Mounting Housing:	PVC Housing Included
Specify Finish/Colour:	Dark Grey / Custom
Input Voltage Option:	100-240VAC / 24VDC
Dimmable Option:	Non-Dimmable / DALI / 1-10V




All product details are subject to change without notice. Final specifications may vary.

toll-free: **1300 295 367**email: **mail@industrialight.com.au**

sales reps:


mobile: **0488 839 917**mobile: **0488 844 503**

Size Options



ALT550R

TRIM DIMENSIONS:
230x195mm



ALT554R

TRIM DIMENSIONS:
255x255mm

