

ALT550S RECESSED IP65 LED WALL LIGHT

ALT550S is a commercial wall light luminaire ideally suited to commercial projects, common areas, corridors and stairway lighting. The fitting features integral constant current LED driver and robust construction with corrosion resistant powdercoat surface treatment. ALT550 series is also available in a recess mount version (ALT550R).

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	18W
LED Driver Classification:	Integral LG-D LED Driver
Light Source Classification:	Citizen SMD LED

MECHANICAL SPECIFICATIONS


Minimum IK Rating:	IK10	
IP Protection Rating:	IP65	
Nominal Dimensions:	255x255mm	
Construction Material:	Cast Aluminium, Powdercoated	
Standard Colour/Finish:	Dark Grey	
Recommended Ambient Temp:	-10 ~ +50°C°	

CONFIGURATION OPTIONS

- Recess mounted version also available (ALT550R)
- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	85lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	60° / Indirect Visor

**Control Options**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	ALT550S
Specify LED CCT:	3000K / 4000K / 6000K
Mounting:	Surface Mounted
Specify Finish/Colour:	Dark Grey / Custom
Input Voltage Option:	100-240VAC / 24VDC
Dimmable Option:	Non-Dimmable / DALI / 1-10V



All product details are subject to change without notice. Final specifications may vary.