

ALT6100 LED POLE LUMINAIRE

ALT6100 is a high-quality pole luminaire that features premium quality LED components. The professional luminaire is fixed onto a powdercoated steel pole and provides excellent area illumination for pathways, carparks and other commercial spaces. ALT6100 is available in a variety of powdercoated colours by special request.


ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	45W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	Epistar COB



MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Head Dimensions:	265x190mm
Construction Material:	Aluminium
Surface Treatment:	Corrosion Resistant
Recommended Ambient Temp:	-15°C - 45°C



CONFIGURATION OPTIONS

- Custom colour refinishing by special request
- Custom pole height by special request



PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	75°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI



ORDERING INFORMATION

Model Number:	ALT6100
Specify LED CCT:	3000K / 4000K / 6000K
Specify Pole Height:	3.5mtrs / Custom
Specify Wattage:	45W
Optional Accessory:	Inground Anchor Bolt Kit
Colour Finish:	Anthracite / Black / Opal Gray / Custom
Control Option:	Non Dim / Wireless / DALI / Casambi



All product details are subject to change without notice. Final specifications may vary.