

AWS600 RECESSED CEILING LUMINAIRE

AWS600 is an adjustable recessed ceiling luminaire with smooth and powerful LED light source. The product is available in single or twin configuration and features a uniquely design adjustable module. AWS is ideal for task lighting projects, retail and showrooms, wall washing, offices and boardrooms, commercial interior lighting.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	19W / 38W
LED Driver Classification:	Constant Current
Light Source Classification:	SMD2835

**MECHANICAL SPECIFICATIONS**

Body Configurations:	Single 125mm / Dual 195mm
IP Protection Rating:	IP20
Dimensions:	600x195mm / 600 x 125mm
Construction Material:	Aluminium
Standard Colour/Finish:	White Powdercoated
Recommended Ambient Temp:	-20°C - 45°C

CONFIGURATION OPTIONS

- Non standard trim colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	95lm/w
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120° / 2x120°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

ORDERING INFORMATION

Model Number:	AWS600
Specify LED CCT:	3000K / 4000K / 6500K
Specify Configuration:	Single / Dual
Specify Wattage:	19W / 38W
Input Voltage Option:	100-240VAC / 24VDC
Dimming Option:	Non-Dimmable / DALI / 1-10V



All product details are subject to change without notice. Final specifications may vary.