


BX70 BX-SERIES® LINEAR LED BATTEN LUMINAIRE

BX-Series® is an industrial grade LED light luminaire suitable for warehouses, storerooms, factories, machinery plants and other industrial applications. Industrialight BX luminaires have a toughened polycarbonate wrap-around opaque diffuser which produces extremely uniform performance for large scale projects.

ELECTRICAL PARAMETERS

Input Voltage:	110-265VAC
Power Consumption:	30W / 55W / 70W / 80W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight SMD2835 LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10	
IP Protection Rating:	IP65	
Nominal Lengths:	600-1500mm	
Construction Material:	Extruded Aluminium	
Diffuser Material:	Opal Polycarbonate (Toughened)	
Recommended Ambient Temp:	-30°C - 55°C	

CONFIGURATION OPTIONS

- Adjustable mounting brackets included
- Custom lengths available by request
- 24VDC version available by special request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	150°

**Control Options**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	BX70
Specify LED CCT:	3000K/4000K/6500K
Specify Beam Angle:	150°
Specify Wattage:	30W / 55W / 70W / 80W
Nominal Luminaire Length:	600/1000/1200/1500mm
Control Options:	Non Dimmable / DALI / 1-10V / Casambi

All product details are subject to change without notice. Final specifications may vary.

