

**CDL332 IP65 LED CEILING LIGHT**

CDL332 is a professional grade LED ceiling light for exterior locations. The compact design and powerful light source make the product suitable for lighting applications. The body is constructed from high pressure die cast aluminium with corrosion resistant powdercoated surface treatment, ideal for commercial or residential projects.

**ELECTRICAL PARAMETERS**

Input Voltage:	220-240VAC
Power Consumption:	5W / 10W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	SMD2835

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK08
IP Protection Rating:	IP65
Nominal Dimensions:	101x30mm
Construction Material:	Die Cast Aluminium
Standard Colour/Finish:	Black / White
Recommended Ambient Temp:	-15°C - 45°C

**TYPICAL APPLICATIONS**

- Ceiling lighting in wet and outdoor areas
- Common areas, foyers, balconies and hallways

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	110°

**CONFIGURATION OPTIONS**

Dimming and control options can be adapted by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming. Available in 5W or 10W LED configuration.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>CDL332</b>
Specify LED CCT:	<b>3000K / 4000K / 6000K</b>
Diffuser Option:	<b>White Opal</b>
Specify Finish/Colour:	<b>Black / White / Custom</b>
Specify Wattage:	<b>5W / 10W</b>
Dimming Option:	<b>Non-Dimmable / DALI</b>



All product details are subject to change without notice. Final specifications may vary.