

**CLS260 SURFACE MOUNT LED CEILING LIGHT**

CLS260 is a vandal resistant LED ceiling light with solid aluminium construction and toughened polycarbonate cover. CLS260 is rated to IP65 and is suitable for all interior or exterior locations. Typical applications include work areas, storage facilities, loading zones, carparks, other commercial lighting applications.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-240VAC
Power Consumption:	12W / 24W / 36W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	SN2865 LED

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK08
IP Protection Rating:	IP65
Nominal Diameter:	200mm / 250mm / 320mm
Construction Material:	Die Cast Aluminium
Standard Colour/Finish:	Black / White
Recommended Ambient Temp:	-20°C - 45°C

**CONFIGURATION OPTIONS**

- Non standard colours available by special request
- DALI dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	100lm/w
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	110°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>CLS260</b>
Specify LED CCT:	<b>3000K / 4000K / 6000K</b>
Specify Diameter:	<b>200mm / 250mm / 320mm</b>
Specify Wattage:	<b>12W / 24W / 36W</b>
Input Voltage Option:	<b>100-240VAC / 24VDC</b>
Dimming Options:	<b>Non Dimmable / DALI / 1-10V Wireless</b>



All product details are subject to change without notice. Final specifications may vary.