

CP1100 RECESSED MOUNT LED CANOPY LUMINAIRE

CP1100 is a slimline, industrial-grade LED canopy luminaire ideal for general area lighting in commercial and industrial spaces. Designed with an architecturally styled, powder-coated steel body and durable polycarbonate lens, it features a powerful, efficient modular LED light source with an integrated LED driver. Multiple optical options are available for versatile lighting solutions.

ELECTRICAL PARAMETERS

Input Voltage:	100-277VAC
Power Consumption:	60W / 100W / 150W
LED Driver Classification:	Integran Constant Current
Light Source Classification:	Philips Lumileds

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Nominal Dimensions:	380x380x70mm
Construction Material:	Aluminium Alloy with PC & Glass
Standard Colour/Finish:	Powdercoated / White
Net Weight:	7.5KG
Recommended Ambient Temp:	-15°C - 50°C

CONFIGURATION OPTIONS

- Recessed version also available
- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	105lm/w
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	90° / 120°

**CONFIGURATION OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	CP1100
Specify LED CCT:	3000K / 4000K / 6500K
Specify Beam Angle:	90° / 120°
Specify Wattage:	80W / 100W / 150W / 200W
Input Voltage Option:	100-277VAC
Control Options:	Non Dimmable / DALI / 1-10V / Sensor

All product details are subject to change without notice. Final specifications may vary.

