

DCR230 DECOR® LED HIGHBAY PENDANT 30W

Decor® LED highbays are industrial pendant light fittings suitable for a wide range of modern interior projects. The DCR luminaires feature decorative prismatic refractor which creates a stylish appearance whilst delivering good optical LED performance.

ELECTRICAL PARAMETERS

Input Voltage:	120-240VAC
Power Consumption:	30W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight XP-LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IKx
IP Protection Rating:	IP44
Nominal Dimensions:	345mm(D) x 350mm(H)
Construction Material:	Polycarbonate Refractor
Standard Colour/Finish:	Anodised Silver
Recommended Ambient Temp:	-35°C - 45°C

**CONFIGURATION OPTIONS**

- Heatsink colour can be refinished by special request
- Wire suspension mounting height can be customised

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	105lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	90°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**CASAMBI****ORDERING INFORMATION**

Model Number:	DCR230
Specify LED CCT:	3000K/4000K/5000K/6500K
Mounting Configuration:	Suspended
Specify Finish/Colour:	Anodised/Prismatic
Specify Wattage:	30W
Dimming Options:	Non Dimmable / DALI / 1-10V / Sensor



All product details are subject to change without notice. Final specifications may vary.