

**DCR288 LED Highbay Pendant Luminaire**


DCR288 is a modern and stylish highbay style luminaire with efficiency heatsink body, class-leading LED technology and stable performance. The design is suitable for modern architectural interiors, schools, retail, warehouse conversions, commercial fitouts, offices and more.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-305VAC
Max Power Consumption:	60W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	CREE

**MECHANICAL SPECIFICATIONS**

Mounting Method:	Suspended
IP Protection Rating:	IP65
Body Dimensions:	288x100mm
Construction Material:	Aluminium
Standard Colour/Finish:	Metallic Silver
Recommended Ambient Temp:	-25°C - 50°C

**CONFIGURATION OPTIONS**

- Heatsink colour can be refinished by special request
- Can be wire or chain suspended

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	125lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	60° / 90° / 120°

**CONTROL OPTIONS**

DCR288 can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>DCR288</b>
Specify LED CCT:	<b>3000K/4000K/5000K/6500K</b>
Mounting Configuration:	<b>Suspended</b>
Optional Accessory:	<b>Wire Suspension Kit</b>
Specify Finish/Colour:	<b>Metallic Silver / Black / White</b>
Specify Power Option:	<b>30W / 60W / 90W</b>
Beam Angle Distribution:	<b>60° / 90° / 120°</b>
Dimming Options:	<b>Non Dim / DALI / Casambi / Sensor</b>

All product details are subject to change without notice. Final specifications may vary.

