

DK600 LED DOCKLIGHT SWING ARM LUMINAIRE

DK600 is an industrial-grade task lighting solution manufactured from robust materials. The multi-pivot arm is available in two size configurations and can be powdercoated in any colour finish by special request. Typical applications include loading docks, factories, delivery zones, manufacturing & processing, inspection facilities.

ELECTRICAL PARAMETERS

Input Voltage:	100-277VAC
Power Consumption:	12W / 23W / 60W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	Philips COB LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Swing Arm Length:	1000mm / 2400mm
Construction Material:	Powdercoated Steel
Standard Colour/Finish:	Signal Yellow
Recommended Ambient Temp:	-30°C - 55°C



KEY FEATURES

- Adjustable Swing Arm + Pivot Luminaire
- Industrial Grade Construction

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	95lm/W
CCT Colour Temperature:	4000K / 6500K
Colour Rendering (Ra):	>95Ra
Beam Angle/Viewing Angle:	85°

CONFIGURATION OPTIONS

DK600 can be customised or configured according to the needs of your project. Swing Arm length can be tailored to suit specific work bays. Is available in single arm or twin arm variants. Signal yellow or Signal Orange powdercoated finish.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	DK600
Specify LED CCT:	4000K / 6500K
Swing Arm Length:	1000mm / 2400mm
Specify Finish/Colour:	Signal Yellow / Signal Orange
Specify Wattage:	12W / 23W / 60W
Arm Configuration	Single Arm or Twin Arm



All product details are subject to change without notice. Final specifications may vary.



toll-free: 1300 295 367

email: 

mail@industrialight.com.au

sales reps:



mobile: 0488 839 917



mobile: 0488 844 503