

DL65 ZHAGA SERIES ARCHITECTURAL LED DOWNLIGHT

Zhaga series is a high-end commercial style LED downlight series that can be used for high end interior projects. The luminaires incorporate high performance Zhaga LED modules and are available in a wide range of beam angle options and other configuration options. Used in commercial spaces, galleries, museums, hospitality, offices, etc.

ELECTRICAL PARAMETERS

Input Voltage:	90-260VAC
Power Consumption:	18W / 25W / 35W
LED Driver Classification:	Constant Current
Light Source Classification:	CREE® Zhaga LED Module

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IKx
IP Protection Rating:	IP20
Nominal Dimensions:	205mm / Cutout: 185mm
Construction Material:	Aluminium
Standard Colour/Finish:	White Trim + Silver Reflector
Recommended Ambient Temp:	-10°C - 55°C

CONFIGURATION OPTIONS

- Non standard trim colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	Various

**CONFIGURATION OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	DL65 - Tilt Adjustable
Specify LED CCT:	3000K/4000K/6500K
Specify Beam Angle:	24° / 40°
Specify Finish/Colour:	White with Silver Reflector
Specify LED Wattage:	18W / 24W / 35W
Specify LED Driver:	Non Dimmable / DALI / DSI / Casambi



All product details are subject to change without notice. Final specifications may vary.