

**EURO156 LED BOLLARD SERIES 156MM**

Industrialight Euro® 156mm LED Bollard is a professional solution for walkways, pathways and security lighting application for a wide range of projects. Euro® LED Bollards are constructed from high strength materials and feature high efficiency LED components and integral LED control gear.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-265VAC
Power Consumption:	20W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	XP-E Power LED

**MECHANICAL SPECIFICATIONS**


Body Diameter:	156mm
IP Protection Rating:	IP65
Overall Height Options:	380mm / 680mm / Custom
Construction Material:	Extruded Alloy/Powdercoated
Standard Colour/Finish:	Black / Opal Grey / Custom
Recommended Ambient Temp:	-20°C - 45°C

**CONFIGURATION OPTIONS**

- 380mm or 680mm Height (Custom Height Also Available)
- 100-265VAC or 24VDC Voltage
- Flat top or Dome Top Options

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	360° Illumination

**CONFIGURATION OPTIONS**

Euro® LED Bollards can be customised or configured according to the needs of your project. Custom powdercoat options. Dimming and control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Series:	<b>EURO 156 LED BOLLARD</b>
Model Numbers:	<b>EUR148(380mm) / EUR166(680mm)</b>
Specify LED CCT:	<b>3000K/4000K/6500K</b>
Specify Top:	<b>Flat or Dome Shape</b>
Specify Finish/Colour:	<b>Black / Silver / White</b>
Height Option:	<b>380mm / 680mm / Custom</b>
Dimming Option	<b>Non Dimmable / DALI / Phase Dimmable</b>



All product details are subject to change without notice. Final specifications may vary.