

EURO760SS LED BOLLARD SERIES 168MM


Industrialight Euro® LED Bollards is a professional solution for walkways, pathways and security lighting application for a wide range of projects. Euro® 760SS LED Bollards are constructed from solid 316L marine grade stainless steel, and offer the highest quality bollard construction available. Euro incorporate high efficiency LED components and integral LED control gear.

ELECTRICAL PARAMETERS

Input Voltage:	100-265VAC
Power Consumption:	12W / 20W
LED Driver Classification	Integral, Constant Current
Light Source Classification:	XP-E Power CREE LED

**MECHANICAL SPECIFICATIONS**

Body Diameter:	168mm
IP Protection Rating:	IP65
Overall Height Options:	760mm
Construction Material:	316L Stainless Steel
Standard Colour/Finish:	Brushed Stainless
Recommended Ambient Temp:	-20°C - 45°C

**CONFIGURATION OPTIONS**

- Custom Height Also Available
- 24VDC Input Voltage by Special Request
- Tunable CCT by Special Request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K/4000K/6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	360° Illumination

**CONFIGURATION OPTIONS****CASAMBI**

Euro® LED Bollards can be customised or configured according to the needs of your project. Custom powdercoat options. Dimming and control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

ORDERING INFORMATION

Series:	EURO760SS (160mm Dia)
Height Option:	760mm / Custom
Specify LED Power:	12W / 20W / Other: _____
Specify LED CCT:	3000K / 4000K / 6500K / CCT Tunable
Specify Top:	100-265VAC or 24VDC
Specify Finish/Colour:	Brushed Stainless / Custom Finish
Optional Accessory:	PE Auto Daylight Switch
Dimming Option	Non Dimmable / DALI / Phase Dimmable

All product details are subject to change without notice. Final specifications may vary.

