

EURO90 LED BOLLARD SERIES 90MM

Industrialight Euro® 90mm LED Bollards is a professional solution for walkways, pathways and security lighting application for a wide range of projects. Euro® LED Bollards are constructed from high strength materials and feature high efficiency LED components and integral LED control gear.

ELECTRICAL PARAMETERS

Input Voltage:	100-265VAC
Power Consumption:	10W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	XP-E Power LED

MECHANICAL SPECIFICATIONS


Body Diameter:	90mm
IP Protection Rating:	IP65
Overall Height Options:	380mm / 680mm / 900mm
Construction Material:	Extruded Alloy/Powdercoated
Standard Colour/Finish:	Black / Opal Grey / Custom
Recommended Ambient Temp:	-20°C - 45°C

CONFIGURATION OPTIONS

- 380mm or 680mm Height (Custom Height Also Available)
- 100-265VAC or 24VDC Voltage
- Flat top or Dome Top Options

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	360° Illumination

CONFIGURATION OPTIONS

Euro® LED Bollards can be customised or configured according to the needs of your project. Custom powdercoat options. Dimming and control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Series:	EURO 90 LED BOLLARD
Model Numbers:	EUR145(380mm) / EUR144(680mm)
Specify LED CCT:	3000K/4000K/6500K
Specify Top:	Flat or Dome Shape
Specify Finish/Colour:	Black / Silver / White
Height Option:	380mm / 680mm / 900mm / Custom
Dimming Option	Non Dimmable / DALI / Phase Dimmable



All product details are subject to change without notice. Final specifications may vary.