

GLINE LINEAR LED PENDANT

GLINE is an architecturally refined, high-end linear pendant luminaire designed to elevate modern interiors. Showcasing unique details and premium integrated LED lighting, it delivers exceptional performance and visual comfort. As an Australian lighting manufacturer, we ensure each GLINE meets rigorous Australian standards for commercial lighting. Trust our Australian lighting products to bring style, efficiency, and innovation to sophisticated environments.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	42W
LED Driver Classification:	Integral Canopy Mounted
Light Source Classification:	SMD LED 2835



MECHANICAL SPECIFICATIONS

Installation:	Wire Suspended
IP Protection Rating:	IP40
Nominal profile Dimensions:	40x60mm
Construction Material:	Extruded Aluminium
Standard Colour/Finish:	White / Matt Silver / Black
Recommended Ambient Temp:	-55°C - 55°C

CONFIGURATION OPTIONS

- Direct / Indirect Configurations Available
- Custom length available by special request
- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	Direct 90°

CONTROL OPTIONS



This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI

ORDERING INFORMATION

Model Number:	GLINE
Specify LED CCT:	2700K / 3000K / 4000K
Specify Luminaire Size:	Custom Length(s)
Specify Wattage:	45W / 60W / 120W
Dimming Option:	DALI/ Non-Dimmable
Mounting Accessories:	Wire Suspension kit / Ceiling Canopy Kit

All product details are subject to change without notice. Final specifications may vary.

