

IDR1200 DIRECT/INDIRECT LED SUSPENDED LUMINAIRE

IDR1200 is an efficient suspended luminaire for commercial and office lighting projects. IDR1200 provides direct illumination and also provides discrete upward indirect illumination. IDR1200 is ideally suited to commercial spaces, workstations, offices, reception areas, education projects.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	2x20W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	SMD2820 LED

MECHANICAL SPECIFICATIONS

Installation Method:	Wire Suspension
IP Protection Rating:	IP40
Nominal Dimensions:	1225x100x50mm
Construction Material:	Aluminum
Standard Colour/Finish:	White & Opal Polycarbonate
Recommended Ambient Temp:	-10°C - 45°C

**CONFIGURATION OPTIONS**

- Surface mounted version available by request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	-150°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**CASAMBI****COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

ORDERING INFORMATION

Model Number:	IDR1200
Specify LED CCT:	3000K / 4000K / 6500K
Specify Length:	1225mm
Specify Wattage:	20W / 40W
Illumination:	Direct-Indirect / Direct-Only
Dimming Options:	Non-Dimmable / DALI / 1-10V / DSI



All product details are subject to change without notice. Final specifications may vary.



toll-free: 1300 295 367

email: mail@industrialight.com.au

sales reps:



mobile: 0488 839 917



mobile: 0488 844 503