

IL2620 COMET RECESSED LED DOWNLIGHT

Comet is a LED downlight luminaire suitable for commercial projects. The fittings feature semi-specular reflector for optimum efficiency and aesthetic. It features integrated LED with professionally designed thermal management system resulting in superior service life. Avail in a range of dimming configurations and sizes from 20W to 50W.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	20W
LED Driver Classification:	Remote Constant Current
Light Source Classification:	Sharp COB LED

MECHANICAL SPECIFICATIONS

IP Protection Rating:	IP44
Trim Diameter:	160mm
Ceiling Cutout:	140mm
Overall Depth:	140mm
Recommended Ambient Temp:	15°C - 45°C



CONFIGURATION OPTIONS

- Non standard trim colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	95lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>95Ra
Beam Angle/Viewing Angle:	60°



CONFIGURATION OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



CASAMBI

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



DIMMING CONFIGURATION

- IL2620 is supplied w/ phase dimmable LED driver
- DALI dimmable LED driver available by special request
- Non-dimmable version available by special request

ORDERING INFORMATION

Model Number:	IL2620
Specify LED CCT:	2700K 3000K / 4000K / 6500K
Specify Wattage:	20W
Specify Finish/Colour:	White / Black
Beam Angle:	60°
Dimming Option:	Phase Dimmable / DALI / Non-Dim

All product details are subject to change without notice. Final specifications may vary.

