

**IL3392 GRID 100 RECESSED LED DOWNLIGHT**

Grid 100 is a high quality recessed LED downlight series. The product is manufactured from premium materials and incorporates high efficiency optic and semi-specular reflector. Grid 100 is available in one, two, and three-gang versions and is suitable for architectural use in both residential and commercial projects.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-240VAC
Power Consumption:	30W
LED Driver Classification:	Remote Mounted
Light Source Classification:	Sharp COB 350mA

**MECHANICAL SPECIFICATIONS**

IP Protection Rating:	IP20
Trim Dimensions:	112x200mm
Ceiling Cutout:	97x187mm
Standard Colour/Finish:	White / Black
Recommended Ambient Temp:	15°C - 45°C

**CONFIGURATION OPTIONS**

- Non standard trim colours available by special request
- DALI dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	2700K / 3000K / 4000K / 6000K
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	25° / 45° / 55°

**CUSTOM OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**CASAMBI****COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**DIMMING CONFIGURATION**

- Phase Dimmable LED Driver Available
- DALI dimmable LED driver available by special request
- Non-dimmable version available by special request

**ORDERING INFORMATION**

Model Number:	<b>IL3392</b>
Specify LED CCT:	<b>2700K / 3000K / 4000K / 6000K</b>
Specify Beam Angle:	<b>25° / 45° / 55°</b>
Specify Wattage:	<b>2x15W</b>
Mutigang:	<b>1-gang / 2-gang / 3-gang Variants</b>
Dimming Option:	<b>Phase Dimmable / DALI / Non-Dimmable</b>

All product details are subject to change without notice. Final specifications may vary.

