


IL3493 GRID 150 RECESSED LED DOWNLIGHT

Grid 150 is a high quality recessed LED downlight series. The product is manufactured from premium materials and incorporates high efficiency optic and semi-specular reflector. Grid 150 is available in one, two, and three-gang versions and is suitable for architectural use in both residential and commercial projects.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	45W
LED Driver Classification:	Remote Mounted
Light Source Classification:	Sharp COB 350mA



MECHANICAL SPECIFICATIONS

Adjustable Function:	Tilt & Swivel	 DIMMABLE
IP Protection Rating:	IP20	
Trim Dimensions:	458x176mm	
Ceiling Cutout:	440x162mm	
Standard Colour/Finish:	White / Black	
Recommended Ambient Temp:	15°C - 45°C	

CONFIGURATION OPTIONS

- Non standard trim colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	90lm/W	
CCT Colour Temperature:	2700K / 3000K / 4000K / 6000K	
Colour Rendering (Ra):	>90Ra	
Beam Angle/Viewing Angle:	45° / 60°	 

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**DIMMING CONFIGURATION**

- GRID-150 is supplied w/ phase dimmable LED driver
- DALI dimmable LED driver available by special request
- Non-dimmable version available by special request

ORDERING INFORMATION

Model Number:	IL3493
Specify LED CCT:	2700K / 3000K / 4000K / 6000K
Specify Beam Angle:	45° / 60°
Specify Wattage:	3x15W
Multigang:	1-gang / 2-gang / 3-gang Variants
Dimming Option:	Phase Dimmable / DALI / Non-Dim

All product details are subject to change without notice. Final specifications may vary.

