

IL4067 STAINLESS STEEL LED DOWNLIGHT

IL4067 is a high quality marine grade LED downlight suitable for all types of projects including harsh & hazardous environments. The downlight is constructed from stabilised polycarbonate body with a genuine solid 316 stainless steel trim. Semi polished reflector with heat tempered clear glass lens.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	11W / 13W / 18W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	COB

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK09
IP Protection Rating:	IP67
Trim Diameter:	130mm
Ceiling Cutout:	125mm
Overall Depth:	155mm
Construction Material:	316 Stainless Steel
Recommended Ambient Temp:	-15°C - 45°C

**CONFIGURATION OPTIONS**


- Stainless steel trim can be powdercoated by request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	105lm/w
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	25° / 60°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	IL4067
Specify LED CCT:	3000K / 4000K / 6000K
Specify Wattage:	11W / 13W / 18W
Specify Finish/Colour:	Stainless Steel / White / Black / Custom
Beam Angle:	25° / 60°
Dimming Option:	DALI / Non-Dimmable / Casambi



All product details are subject to change without notice. Final specifications may vary.