

IL4770 SURFACE MOUNT LED SPOTLIGHT

IL4770 is a modern adjustable spotlight ideally suited for commercial projects. The fitting features an integral LED driver and delivers strong light output and optical performance. IL4770 is IP65 rated and is suitable for indoor or outdoor projects.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	18W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	18W COB LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10	 DIMMING OPTIONAL
IP Protection Rating:	IP65	
Nominal Dimensions:	316x120mm	
Construction Material:	Extruded Alloy Construction	
Standard Colour/Finish:	Corrosion Resistant	
Recommended Ambient Temp:	-15°C - 45°C	

CONFIGURATION OPTIONS

- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	105lm/w	 
CCT Colour Temperature:	3000K / 4000K / 6500K	
Colour Rendering (Ra):	>85Ra	
Beam Angle/Viewing Angle:	10° / 30° / 60°	

CONFIGURATION OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**CASAMBI****COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	IL4770
Specify LED CCT:	3000K / 4000K / 5700K
Specify Beam Angle:	15° / 30° / 60°
Specify Finish/Colour:	Black / White
Input Voltage Option:	100-240VAC / 24VDC
Dimming Option:	Non Dimmable / DALI / Phase / Casambi



All product details are subject to change without notice. Final specifications may vary.

toll-free: **1300 295 367**email: **mail@industrialight.com.au**

sales reps:

mobile: **0488 839 917**mobile: **0488 844 503**