

**IL9210 AERO MAX LED WALL-WASHER LUMINAIRE**

Aero-Max fitting is a high powered LED washer fitting ideally suited to large-scale highlighting of buildings, façade lighting and features, commercial wall grazing, and other exterior or interior lighting applications, available in either 500mm or 1000mm nominal lengths and has built in LED control gear. Single colour and RGB+DMX colour control versions are available.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-240VAC
Power Consumption:	36W / 72W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	CREE XPE

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK09
IP Protection Rating:	IP65
Profile Dimensions:	100x100mm
Construction Material:	Aluminium
Standard Colour/Finish:	Graphite
Recommended Ambient Temp:	-20°C~+50°C

**CONFIGURATION OPTIONS**

- Non standard colours available by special request
- DALI or DMX dimmable LED driver available by request
- Custom lengths available by special request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K/ RGB
Colour Rendering (Ra):	>85
Beam Angle/Viewing Angle:	36° x 60°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>IL9210 Aero-Max</b>
Specify LED CCT:	<b>3000K / 4000K / 6000K/ RGB</b>
Specify Wattage:	<b>36W / 72W</b>
Specify Length:	<b>500mm / 1000mm</b>
Input Voltage Option:	<b>100-240VAC / 12VDC / 24VDC</b>
Control Options:	<b>Non Dimmable / DALI / Casambi / DMX</b>



All product details are subject to change without notice. Final specifications may vary.