

IL9220 AERO MAX LED WASHER

Aero Fitting is a high powered LED washer fitting suited to indirect uplighting, architectural illumination of buildings, facade lighting, commercial wall grazing, and other exterior or interior lighting applications. Industrialight Aero is available in either 290mm or 510mm nominal lengths and features built in LED driver.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	12W / 24W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	CREE XPE

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK09
IP Protection Rating:	IP65
Nominal Dimensions:	135x65mm
Construction Material:	Aluminium
Standard Colour/Finish:	Graphite
Recommended Ambient Temp:	-20°C~+50°C

**CONFIGURATION OPTIONS**


- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	30°

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	IL9220 Aero
Specify LED CCT:	3000K / 4000K / 6000K
Specify Wattage:	12W / 24W
Specify Length/Size:	290mm / 510mm
Input Voltage Option:	100-240VAC / 12VDC / 24VDC
Control Options:	Non Dimmable / DALI / Casambi / DMX



All product details are subject to change without notice. Final specifications may vary.