

IL9610 LED Billboard Floodlight Luminaire

IL9610 is a high quality architectural fitting especially designed for billboard and signage lighting. The product features a tilt adjustable head with 500mm pole and mounting bracket. IL9610 incorporates integral LED driver and exceeds IP65 protection rating for all indoor and outdoor applications.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	16W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	CREE SMD3014

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK09
IP Protection Rating:	IP65
Nominal Dimensions:	207x140x70mm
Construction Material:	Aluminium
Standard Colour/Finish:	Matt Silver
Recommended Ambient Temp:	-10°C~+40°C

**CONFIGURATION OPTIONS**

- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	85lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	100°

CONFIGURATION OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	IL9610
Specify LED CCT:	3000K / 4000K / 6500K
Specify Wattage:	16W
Specify Pole Length:	500mm / Custom
Colour/Finish:	Matt Silver / Black / White
Input Voltage Option:	100-240VAC / 12VDC / 24VDC
Control Options:	Non Dimmable / DALI / Casambi / DMX

All product details are subject to change without notice. Final specifications may vary.

