



IPW160 CUBE WALL LUMINAIRE

IPW160 is a professional integrated LED wall light suitable for commercial projects. IPW160 features corrosion resistant construction with high lumen output and optical performance. Ideally suited to shopping malls, public spaces, courtyards, building facades, education projects, commercial projects.

ELECTRICAL PARAMETERS

Input Voltage:	110-240VAC
Power Consumption:	18W
LED Driver Classification:	Integral 700mA LED Driver
Light Source Classification:	CREE CXA 1507


MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK09	 DIMMING OPTIONAL
IP Protection Rating:	IP65	
Nominal Dimensions:	160x73x100mm	
Construction Material:	Die-Cast Alloy + Tempered Glass	
Standard Colour/Finish:	Silver/Black	
Recommended Ambient Temp:	-10 ~ +45°C	 IP65

CONFIGURATION OPTIONS

- Non standard fitting colours and finishes available
- DALI dimmable configuration available by special request
- Custom size and optical distributions available

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/W	
CCT Colour Temperature:	2700K / 3000K / 4000K	
Colour Rendering (Ra):	>85Ra	
Beam Angle/Viewing Angle:	24° / 24° / 36°	

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	IPW160
Specify LED CCT:	2700K / 3000K / 4000K
Specify Beam Angle:	24° / 24° / 36°
Specify Finish/Colour:	Black / Silver / Custom
Input Voltage Option:	240VAC / 24VDC / Custom
Dimming Option:	DALI / Non Dimmable / Other



All product details are subject to change without notice. Final specifications may vary.