

**IXR200S SURFACE-MOUNT LED CANOPY LIGHT**

IXR is a professional surface mounted LED canopy floodlight which can be used for general purpose commercial lighting, floodlighting, highbay/ lowbay lighting, tunnel lighting and other industrial lighting applications. The luminaires have modular LED light source and are available in various models including custom sizes by request.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-305VAC
Power Consumption:	200W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Luxeon® T-Chip LED

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IKx
IP Protection Rating:	IP65
Nominal Dimensions:	303 x 473 x 183mm
Construction Material:	Powdercoated Alloy
Standard Colour/Finish:	Black / Silver / White
Recommended Ambient Temp:	-25°C - 45°C

**CONFIGURATION OPTIONS**

- Also available in 24VDC version
- Frame colour can be refinished
- 1-10V dimmable option by special request
- Custom frame sizes available by special request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>75Ra
Beam Angle/Viewing Angle:	100°

**CONFIGURATION OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**CASAMBI****ORDERING INFORMATION**

Model Number:	<b>IXR200S (200W)</b>
Specify LED CCT:	<b>3000K/4000K/5000K/6500K</b>
Optional Mounting:	<b>Adjustable Pole-Mount Bracket</b>
Specify Finish/Colour:	<b>Black or White</b>
Input Voltage Option:	<b>100-305VAC 24VDC</b>
Control Options:	<b>Non Dimmable / DALI / Casambi / 1-10V</b>

All product details are subject to change without notice. Final specifications may vary.