

IXR40S SURFACE-MOUNT LED CANOPY LIGHT

IXR is a professional surface mounted LED canopy floodlight which can be used for general purpose commercial lighting, floodlighting, highway/ lowbay lighting, tunnel lighting and other industrial lighting applications. The luminaires have modular LED light source and are available in various models including custom sizes by request.



ELECTRICAL PARAMETERS

Input Voltage:	100-305VAC
Power Consumption:	40W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Luxeon® T-Chip LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IKx
IP Protection Rating:	IP65
Nominal Dimensions:	303 x 151 x 183mm
Construction Material:	Powdercoated Alloy
Standard Colour/Finish:	Black / Silver / White
Recommended Ambient Temp:	-25°C - 45°C



CONFIGURATION OPTIONS

- Also available in 24VDC version
- Frame colour can be refinished
- 1-10V dimmable option by special request
- Custom frame sizes available by special request



PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>75Ra
Beam Angle/Viewing Angle:	100°



CONFIGURATION OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI



ORDERING INFORMATION

Model Number:	IXR40S (40W)
Specify LED CCT:	3000K/4000K/5000K/6500K
Optional Mounting:	Adjustable Pole-Mount Bracket
Specify Finish/Colour:	Black or White
Input Voltage Option:	100-305VAC 24VDC
Control Options:	Non Dimmable / DALI / Casambi / 1-10V

All product details are subject to change without notice. Final specifications may vary.