

IXT80W INDUSTRIAL LED CANOPY/FLOODLIGHT

IXT is the latest generation in Industrial lighting. Constructed from corrosion resistant aluminium materials, with advanced modular LED light source. IXT delivers superior lumen performance and is an ideal lighting solution for canopy lighting, carparks, harsh environments, building facades, security lighting, general purpose floodlighting, industrial sites, commercial projects.

ELECTRICAL PARAMETERS

Input Voltage:	85-300VAC
Power Consumption:	80W
LED Driver Classification:	Integral
Light Source Classification:	Osram 3030T

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10	
IP Protection Rating:	IP65	
Nominal Dimensions:	291x277x62mm	
Construction Material:	Aluminium	
Standard Colour/Finish:	Anodised / Corrosion Resistant	
Recommended Ambient Temp:	-30°C - 55°C	

**CONFIGURATION OPTIONS**


- Several illumination optic / beam angle configs available
- 24VDC version available by special request
- DALI dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	130lm/w	
CCT Colour Temperature:	3000K / 4000K / 6000K	
Colour Rendering (Ra):	>80Ra	
Beam Angle/Viewing Angle:	60° / 90° / 120° / 120°x90° / 150°x80°	

CONFIGURATION OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

ORDERING INFORMATION

Model Number:	IXT80
Specify LED CCT:	3000K / 4000K / 6000K
Specify Beam Angle:	30° / 60° / 90° / 120° / 120°x90° / 150°x80°
Specify Wattage:	80W
Input Voltage Option:	100-305VAC 24VDC
Control Options:	Non Dimmable / DALI / Casambi / 1-10V

All product details are subject to change without notice. Final specifications may vary.

