

KWL501 IP65 LED WALL LUMINAIRE

KWL501 is a high-quality LED luminaire, constructed from extruded aluminium with corrosion resistant powdercoated surface. KWL501 is suited to commercial and domestic projects where a high quality product is required.

ELECTRICAL PARAMETERS

Input Voltage:	220-240VAC	
Power Consumption:	6W	
LED Driver Classification:	LED Logic, Constant Current	
Light Source Classification:	CREE CXA2501 (12W) COB	

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK09	
IP Protection Rating:	IP65	
Overall Height:	140mm	
Body Diameter:	90mm	
Overall Projection From Wall:	118mm	
Construction Material:	Aluminium with Glass Visor	
Standard Colour/Finish:	Black / White / Silver / Custom	
Recommended Ambient Temp:	-15°C - 55°C	

CONFIGURATION OPTIONS

- Non standard colours available by special request
- Remote mounted DALI dimmable LED driver available

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	115lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	10° / 30° / 60°

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	KWL501 DOWN
Specify LED CCT:	3000K / 4000K / 6000K
Specify Beam Angle:	10° / 30° / 60°
Specify Finish/Colour:	Black / White / Other
Input Voltage Option:	240VAC / 24VDC
Dimmable Option:	Non Dimmable / DALI / Casambi

All product details are subject to change without notice. Final specifications may vary.