

LAUNCH 300 SURFACE LINEAR LED LUMINAIRE

Launch 300 is a modern surface-mounted LED light luminaire with advanced design and features. The product incorporates an impact resistant body, polycarbonate diffuser and an integral constant current LED driver. Launch 300 is ideally suited for projects where a stylish surface mounted option is required. Typical applications include offices, workspaces, retail and showrooms, education projects, carparks, storage areas and other commercial projects.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	8W / 15W / 22W / 30W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	SMD2835 LED

MECHANICAL SPECIFICATIONS



IP Protection Rating:	IP44
Nominal Dimensions:	108mm / 168mm / 220mm / 300mm
Overall Depth:	39mm
Construction Material:	Die Cast Aluminium
Standard Colour/Finish:	Powdercoated White / Black
Recommended Ambient Temp:	-15°C - 45°C

CONFIGURATION OPTIONS

- Non standard colours available by special request
- Phase dimmable or DALI dimmable LED driver available

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/w
CCT Colour Temperature:	3000K / 4000K / 5000K / 6000K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	115°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

ORDERING INFORMATION

Model Number:	Launch 300
Specify LED CCT:	3000K / 4000K / 5000K / 6000K
Specify Size (Square):	108mm / 168mm / 220mm / 300mm
Wattage Option:	8W / 15W / 22W / 30W
Dimming Configuration:	Phase Dimmable / Non-Dim / DALI
Input Voltage:	100-240VAC



All product details are subject to change without notice. Final specifications may vary.