

## LCS206 LED LANDSCAPE SPOTLIGHT

LCS206 is a premium quality landscape fitting for garden lighting, pathway lighting, task lighting and discrete illumination of other landscape features. The fitting is constructed from steel and finished with a corrosion resistant bronze plating or anodised surface treatment. LCS206 is supplied with garden spike for versatile installation. Several other mounting options are also available.

### ELECTRICAL PARAMETERS

Input Voltage:	12VDC / 24VDC / 240VAC
Power Consumption:	6W / 10W
LED Driver Classification:	Integral or Remote Mounted
Light Source Classification:	CREE CXA1507



### MECHANICAL SPECIFICATIONS

IP Protection Rating:	IP67	
Dimensions - Body Diameter	58mm	
Dimensions - Body Length	95mm	
Overall Height:	300mm including Spike	
Construction Material:	Plated with High Corrosion Resistance	
Standard Colour/Finish:	Silver Plated / Aged Bronze	
Recommended Ambient Temp:	-20°C - 50°C	

### CONFIGURATION OPTIONS

- Non standard colours available by special request
- DALI dimmable LED driver available by request
- RGB/RGBW control options available by request



### PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	95lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K / RGB
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	30° / 60°



### CONTROL OPTIONS

LCS series can be supplied in 12VDC, 24VDC or 240VAC options. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

### COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI



### ORDERING INFORMATION

Model Number:	LCS206 (Spike Version)
Specify LED CCT:	3000K / 4000K / 6500K
Specify Beam Angle:	30° / 60°
RGB/W Configuration:	RGB / RGBW
Input Voltage Option:	12VDC / 24VDC / 240VAC
Specify Wattage:	6W / 10W

All product details are subject to change without notice. Final specifications may vary.

