

LIDO-76 INGROUND LINEAR LED LUMINAIRE

LIDO-76 is a premium recessed linear luminaire engineered for high-performance architectural lighting. Featuring a precision glass diffuser for smooth, uniform illumination and marine-grade construction for superior corrosion resistance, it is ideal for coastal, commercial, and high-end residential projects requiring durable, refined LED lighting solutions.

ELECTRICAL PARAMETERS

Input Voltage:	24VDC
Power Consumption:	16W / 33W
LED Driver Required:	24VDC Constant Voltage
Light Source Classification:	3525 SMD LED



MECHANICAL SPECIFICATIONS

Mounting Options:	Inground / Recessed
IP Protection Rating:	IP67
Diffuser Configuration:	Opal Glass
Length Options:	550mm / 1050mm
Profile Dimensions:	76mm(W) x 30mm(D)
Trim Material:	316 Marine Grade Stainless Steel
Recommended Ambient Temp:	-35°C - 55°C

CONFIGURATION OPTIONS

- Custom lengths available by special request
- Remote mounted DALI Driver by request
- RGBW and CCT TUNable Options by special request
- Trim can be powdercoated by special request
- Custo, interconnect cables by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	120°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



CASAMBI

COMPLIANCE & CERTIFICATION

IESNA2002
EMC Compliant, LM79, LM80
Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	LIDO76
Specify LED CCT:	3000K/4000K/5000K/6500K
Specify Size Option:	550mm L / 1050mm L
Input Voltage Option:	24VDC
Optional LED Driver:	Non Dimmable / DALI / Tunable DT8

All product details are subject to change without notice. Final specifications may vary.



toll-free: 1300 295 367



email: mail@industrialight.com.au

sales reps:



mobile: 0488 839 917



mobile: 0488 844 503



