

LIDO-K120 RECESSED LINEAR INGROUND UPLIGHT

LIDO-K120 is a premium quality inground luminaire available in several linear configurations. The luminaire is ideal for facade lighting and architectural feature lighting for commercial and landscape projects. Lido features a genuine 316 stainless steel trim and tempered toughened glass lens.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-240VAC
Power Consumption:	11W / 22W / 32W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	CREE XP-E2

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP67
Length Options:	350mm / 650mm / 920mm
Dimensions:	97(w)x120(d)
Construction Material:	Stainless Steel
Recommended Ambient Temp:	-35°C - 55°C

CONFIGURATION OPTIONS

- 24VDC version available by special request
- DALI LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K / 4000K / 5700K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120°

**CONTROL OPTIONS**


This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**CASAMBI****COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	LIDO-K120
Specify LED CCT:	3000K / 4000K / 5700K
Specify Length:	350mm / 650mm / 900mm
Specify Wattage:	11W / 22W / 32W
Input Voltage Option:	100-240VAC / 24VDC
Control Option:	Non Dimmable / DALI / 1-10V / Casambi



All product details are subject to change without notice. Final specifications may vary.