

**LPS7718 POLE MOUNTED LANDSCAPE LED**

LPS7718 is a pole mounted luminaire which features extruded aluminium construction and corrosion resistant powdercoat surface treatment. The unique design incorporates a 360-degree anodised aluminium reflector and diffused LED light source that delivers smooth indirect illumination. LPS7718 also features a clear polycarbonate visor which enhances vandal resistance.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-240VAC
Power Consumption:	35W / 45W
LED Driver Classification:	Integral 700mA
Light Source Classification:	CREE XT-E2

**MECHANICAL SPECIFICATIONS**

Height:	3.0mtr
IP Protection Rating:	IP65
Body Diameter:	186mm
Construction Material:	Extruded Alloy + Steel
Diffuser Material:	Toughened PMMA Clear
Recommended Ambient Temp:	-20°C - 45°C

**CONFIGURATION OPTIONS**

- Non standard trim colours available by special request
- DALI dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	85lm/W
CCT Colour Temperature:	3000K / 4000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	360° x 120°

**CONFIGURATION OPTIONS****CASAMBI**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>LPS7718</b>
Specify LED CCT:	<b>3000K / 4000K</b>
Specify Luminaire Height:	<b>3mtr</b>
Specify Finish/Colour:	<b>Black / Matt Silver / Custom</b>
Specify Wattage:	<b>35W / 45W</b>
Input Voltage Option:	<b>100-240VAC or 24VDC</b>
Optional Inground Kit:	<b>LPS7718-AKIT</b>

All product details are subject to change without notice. Final specifications may vary.

