

LPS893 ARCHITECTURAL POLE-MOUNT LED LUMINAIRE

LPS LED LUMINAIREs are high quality architectural luminaires designed for parks & recreational areas, streetlighting, public landscaping, carparks etc. The luminaires have a high-quality integral LED light source and built-in electronic LED control gear. They are supplied with standard pole configurations and height or colour can be customised by request.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	39W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	CXA2530 LED

MECHANICAL SPECIFICATIONS

Pole Height:	3.5mtr
IP Protection Rating:	IP65
Head Diameter:	615mm
Construction Material:	Extruded Alloy + Steel
Diffuser Material:	Toughened PMMA Opal
Recommended Ambient Temp:	-20°C - 45°C

CONFIGURATION OPTIONS

- Can be finished in matt black or matt silver
- Non-standard colour finishes available by special request
- Optional inground concrete J-Bolt anchor kit available

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/w
CCT Colour Temperature:	3000K/4000K/5000K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120°

CONTROL OPTIONS**CASAMBI**

LPS893 can be supplied with custom pole heights, configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	LPS893
Specify LED CCT:	3000K/4000K/5000K
Specify Wattage:	39W
Specify Finish/Colour:	Black / Silver
Optional Inground Kit:	LPS893-AKIT
Control Option:	Non Dimmable / DALI / Sensor / Casambi

All product details are subject to change without notice. Final specifications may vary.

