

M720 WALL MOUNTED LED LUMINAIRE

M720 is a high quality linear LED wall luminaire suitable for commercial and residential spaces. The fitting is available in a wide range of configurations and finishes. Available with single or dual LED light source illumination options.


ELECTRICAL PARAMETERS

Input Voltage:	220-240VAC
Power Consumption:	6W / 12W / 24W
LED Driver Classification:	Integral Constant Voltage
Light Source Classification:	SMD LED



MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08
IP Protection Rating:	IP20
Profile Dimensions:	50x72mm
Construction Material:	Extruded Aluminium
Standard Colour/Finish:	White / Black / Silver
Recommended Ambient Temp:	-15°C - 45°C



CONFIGURATION OPTIONS

- Non standard colours available by special request
- Custom sizes by special request
- Integral DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	2700K / 3000K / 4000K / 6500K
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	2x120°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION



- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

ORDERING INFORMATION

Model Number:	M720
Specify LED CCT:	2700K / 3000K / 4000K / 6500K
Specify Length:	300mm / 600mm / 1200mm
Specify Finish/Colour:	Black / White / Silver
Specify Configuration:	Down Only
Dimming Option:	Non-Dim / DALI Dimmable / RF Control



All product details are subject to change without notice. Final specifications may vary.