INDUSTRALIGHT

MK679 MAKO® LED LUMINAIRE TRUNNION POLE MOUNT

MK679 MAKO® series is a new generation commercial luminaire with professional grade LED components and design. The sleek body and versatile mounting options make it suitable for use in carparks, tennis courts, security lighting, wall mounted lighting, sports fields, general area floodlighting, sensor automation, and more. MAKO® is available in several body sizes and mounting hardware and brackets are modular.

MK679 with MK679-TRB1 U-Bracket
PA2TR Pole Top Adaptor

ELECTRICAL PARAMETERS

Input Voltage:	100-277VAC
LED Power:	180W / 200W / 230W / 250W
LED Driver Classification:	Integrated MK Constant Current
Light Source Classification:	Lumileds Modular SMD LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP66
Nominal Dimensions:	679x350x56mm
Construction Material:	Aluminium Housing with Cooling
Standard Colour/Finish:	Matt Silver / Black / White
Recommended Ambient Temp:	-40°C - 50°C

IMPACT IP66

CONFIGURATION OPTIONS

- Can be fitted with integrated motion sensor or Photo PE cell.
- Compatible with centralised control and network systems
- Wall mount, bracket mount or pole mounted options
- LED light panel is field rotatable to customise on site

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	170lm/W or 145lm/W
Colour Rendering (Ra):	>80Ra
Distribution Option:	IES Type III / Type IV /Type V

CONTROL OPTIONS

CASAMBI DALI

Optional NEMA socket allows for plug in PE cell and/or motion sensor for automation. Other control options are available by special request. Control protocols include DALI, Casambi, Wireless Networking and more. Contact Industralight for more options.

COMPLIANCE & CERTIFICATION

- IESNA2002, DLC Listed, UL:E354989
- AS/NZS60598, LM79-08, LM80, LED Tj <85°
- Lifespan: Exceeds 100,000hrs @ L70
- Lifespan: Exceeds 50,000hrs @ L90

DIMMING OPTIONAL

ORDERING INFORMATION

Model Number:	**MK679T POLE TRUNNION MOUNT**
Specify Power Option:	**180W / 200W / 230W / 250W**
Specify LED CCT:	**3000K / 4000K / 5000K / 6500K**
Specify Light Distribution:	**Type III / Type IV / Type V / TVWQ**
Specify Finish/Colour:	**Black / White / Matt Silver**
Input Voltage Option:	**100-240VAC or 24VDC**
Specify Mounting:	**Pole / Bracket / Wall Mounted**

All product details are subject to change without notice. Final specifications may vary.

WWW.INDUSTRALIGHT.CO.NZ
WWW.INDUSTRALIGHT.COM.AU

toll-free: 1300 295 367 email: mail@industralight.com.au sales reps: mobile: 0488 839 917 mobile : 0488 844 503