

**MTR948 SECTOR LED PATHWAY LIGHT**

MTR948 is a commercial grade inground luminaire designed for public spaces, driveways, commercial landscape lighting and pathway illumination. The body is constructed from die cast alloy with corrosion resistant powdercoated surface treatment. MTR features professional LED light source with integrated LED driver.

**ELECTRICAL PARAMETERS**

Input Voltage:	220-240VAC
Power Consumption:	36W
LED Driver Classification:	Integral LED Driver
Light Source Classification:	Edison LED

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP67
Overall Diameter:	260mm
Overall Mounting Depth:	205mm
Standard Colour/Finish:	Dark Grey
Recommended Ambient Temp:	-15°C - 45°C

**CONFIGURATION OPTIONS**

- Non standard colours available by special request
- DALI dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	85lm/W
CCT Colour Temperature:	3000K / 4000K / 5000K / 6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	115°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>MTR948</b>
Sector Configuration:	<b>4-Way</b>
Specify LED CCT:	<b>3000K / 4000K / 6000K</b>
Wattage:	<b>15W</b>
Specify Input Voltage:	<b>220-240VAC / 12VDC</b>
Specify Finish/Colour:	<b>Dark Grey / Black / White / Custom</b>
Included Accessory:	<b>Inground Housing (included)</b>
Dimming Option:	<b>Non Dimmable / DALI / Phase</b>

All product details are subject to change without notice. Final specifications may vary.

