

NDR RECESSED ASYMMETRIC LED WALL WASHER

NDR is a linear recessed LED LUMINAIRE with unique asymmetrical reflector design suitable for indirect wall washing and task lighting applications. The NDR is suitable for recess-mounting into t-bar or standard plaster-style ceilings.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	40W / 80W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight SMD3310 LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IKx
IP Protection Rating:	IP20
Nominal Luminaire Lengths:	595mm / 1195mm
Construction Material:	Powdercoated Steel
Standard Colour/Finish:	White / Silver/Black
Recommended Ambient Temp:	-10 ~ +55°C



CONFIGURATION OPTIONS

- 1195mm or 595mm nominal dimensions
- Available in 295mm or 150mm nominal luminaire width
- DALI dimmable version available
- 0-10V analogue dimmable version by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120°



CONFIGURATION OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI



ORDERING INFORMATION

Model Number:	NDR Series - Recessed Mounted
Specify LED CCT:	3000K/4000K/5000K/6500K
Specify Ceiling Type:	T-Bar or Plaster Ceiling
Specify Finish/Colour:	White / Brushed Silver
Luminaire Length:	595mm or 1195mm
Specify Luminaire Width:	295mm or 150mm
Dimming Option:	Optional DALI Dimmable

All product details are subject to change without notice. Final specifications may vary.

