

**NP200G NEPTUNE LED BUNKER - GRILLE**

Neptune is a strong impact resistant light fitting featuring a professional LED light source and integral constant current LED driver. NP200 is also available in two sizes and a variety of fascia designs including eyelid and grille options. Typical applications include mining & industrial sites, government projects, education facilities, other commercial and industrial projects.

**ELECTRICAL PARAMETERS**

Input Voltage:	220-240VAC
Power Consumption:	9W-46W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	OEM SMD2835

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK08 / IK10
IP Protection Rating:	IP65
Nominal Dimensions:	214x130mm / 275x180mm / 340x210mm
Construction Material:	Die Cast Aluminium
Standard Colour/Finish:	Corrosion Resistant
Rec Ambient Temp:	-20°C - 55°C

**CONFIGURATION OPTIONS**

- Also available with plain opal or eyelid fascia version
- Non standard colours available by special request
- DALI dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	90lm/w
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**CASAMBI****ORDERING INFORMATION**

Model Number:	<b>NP200G</b>
Specify LED CCT:	<b>3000K / 4000K / 6500K</b>
Facia Version:	<b>Grille</b>
Size Configuration:	<b>214mm / 275mm / 340mm</b>
Wattage Option:	<b>9W / 18W / 24W / 28W / 35W / 46W</b>
Control Option:	<b>Non Dimmable / DALI / 1-10V / Casambi</b>



All product details are subject to change without notice. Final specifications may vary.