

## NP200P NEPTUNE LED BUNKER

Neptune is a strong impact resistant light fitting featuring a professional LED light source and integral constant current LED driver. NP200 is also available in two sizes and a variety of fascia designs including eyelid and grille options. Typical applications include mining & industrial sites, government projects, education facilities, other commercial and industrial projects.

### ELECTRICAL PARAMETERS

Input Voltage:	220-240VAC
Power Consumption:	9W-46W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	OEM SMD2835



### MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08 / IK10
IP Protection Rating:	IP65
Nominal Dimensions:	214x130mm / 275x180mm / 340x210mm
Construction Material:	Die Cast Aluminium
Standard Colour/Finish:	Corrosion Resistant
Rec Ambient Temp:	-20°C - 55°C



### CONFIGURATION OPTIONS

- Also available with plain opal or eyelid fascia version
- Non standard colours available by special request
- DALI dimmable LED driver available by request

### PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120°



### CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

### COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI



### ORDERING INFORMATION

Model Number:	NP200P
Specify LED CCT:	3000K / 4000K / 6500K
Facia Version:	Plain Opal
Size Configuration:	214mm / 275mm / 340mm
Wattage Option:	9W / 18W / 24W / 28W / 35W / 46W
Control Option:	Non Dimmable / DALI / 1-10V / Casambi

All product details are subject to change without notice. Final specifications may vary.

