

NP400P NEPTUNE LED BUNKER

Neptune is a strong impact resistant light fitting featuring a professional LED light source and integral constant current LED driver. It is also available in several sizes and a variety of fascia designs including eyelid and grille options. Typical applications include mining & industrial sites, government projects, education facilities, other commercial and industrial projects.

ELECTRICAL PARAMETERS

Input Voltage:	220-240VAC
Power Consumption:	18W / 24W / 46W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	OEM SMD2835



MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08 / IK10
IP Protection Rating:	IP65
Nominal Dimensions:	270x270mm / 360x360mm
Construction Material:	Die Cast Aluminium
Standard Colour/Finish:	Corrosion Resistant
Recommended Ambient Temp:	-20°C - 55°C



CONFIGURATION OPTIONS

- Also available with grille or eyelid fascia version
- Smaller 130x130mm size available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	90lm/w
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI



ORDERING INFORMATION

Model Number:	NP400P
Specify LED CCT:	3000K / 4000K / 6500K
Facia Version:	Plain Opal
Size Configuration:	270x270mm / 360x360mm
Wattage Option:	18W / 24W / 46W
Control Option:	Non Dimmable / DALI / 1-10V / Casambi

All product details are subject to change without notice. Final specifications may vary.

