

NSR RECESSED ASYMMETRIC LED WALL WASHER

SNR1200 is a contemporary architectural LED LUMINAIRE that can be surface-mounted or suspended in offices and other commercial environments. The SNR1200 features a low-glare louvre insert and high quality integrated LED light source. They are ideal for general purpose lighting or task-lighting applications.

ELECTRICAL PARAMETERS

Input Voltage:	100-260VAC
Power Consumption:	40W / 80W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight SMD3310 LED

MECHANICAL SPECIFICATIONS



Installation:	Surface Mounted
IP Protection Rating:	IP20
Nominal Luminaire Lengths:	1200mm
Construction Material:	Steel w/ Aluminium Reflector
Standard Colour/Finish:	White Powdercoated
Recommended Ambient Temp:	-10°C - 45°C

CONFIGURATION OPTIONS

- Surface-mounted or suspended mounting options
- DALI dimmable version available
- 0-10V analogue dimmable version by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6000K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	100°

CONTROL OPTIONS



This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

CASAMBI



ORDERING INFORMATION

Model Number:	SNR1200
Specify LED CCT:	3000K/4000K/5000K/6000K
Specify Installation Type:	Surface Mounted/Wire Suspension
Specify Finish/Colour:	White / Silver
Specify Luminaire Power:	40W (optional 80W by request)
Control Option:	Non Dimmable / DALI / 1-10V / Casambi



All product details are subject to change without notice. Final specifications may vary.