

## P10230 TUBULAR LED PENDANT

Tubular LED pendant is a stylish modern fitting for residential or commercial interior projects. The fitting is designed with a slimline form factor, high grade powdercoat body with integrated contact current LED driver. Industrialight can manufacture custom configurations of the pendant series, including special colour finishes to suit any décor or project.

### ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	30W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	CREE COB



### MECHANICAL SPECIFICATIONS

Cable Drop Length:	1mtr (Can be Customised)
IP Protection Rating:	IP20
Body Dimensions:	90x220mm
Construction Material:	Extruded Aluminum
Standard Colour/Finish:	Black / White
Recommended Ambient Temp:	15°C - 45°C

### CONFIGURATION OPTIONS

- Non standard colours available by special request
- Custom-made sizes available by special request
- Integral phase dimmable LED driver available by request

### PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	10° / 24° / 38° / 20° / 60°

### CONTROL OPTIONS



This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

### COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**CASAMBI**

### ORDERING INFORMATION

Model Number:	<b>P10230</b>
Specify LED CCT:	<b>3000K / 4000K / 5000K</b>
Specify Beam Angle:	<b>10° / 24° / 38° / 20° / 60°</b>
Specify Finish/Colour:	<b>White / Black</b>
Dimensions:	<b>90x220mm</b>
Control Option:	<b>Non Dimmable / DALI / 1-10V / Casambi</b>

All product details are subject to change without notice. Final specifications may vary.

