

PHB200 ARCHITECTURAL LED HIGHBAY

PHB200 is an architecturally styled LED Highbay luminaire for high-end projects. The fitting features a solid alloy construction with tempered glass visor. The architectural design makes the product ideal for industrial or commercial environments, gymnasiums, entertainment venues, shopping malls and arcades, other commercial projects. PHB200 is also available in a variety of size configurations.

ELECTRICAL PARAMETERS

Input Voltage:	85-266VAC
Power Consumption:	200W
LED Driver Classification:	Integral
Light Source Classification:	High Power T20 LED



MECHANICAL SPECIFICATIONS

Installation:	Suspended or Bracket Mount
IP Protection Rating:	IP65
Body Dimensions:	520x490mm
Construction Material:	Die cast Aluminium
Standard Colour/Finish:	Corrosion Resistant
Recommended Ambient Temp:	-40°C - 50°C

CONFIGURATION OPTIONS

- Also available in smaller sizes, 30W / 50W / 100W,
- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	80°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



CASAMBI

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	PHB200
Specify LED CCT:	3000K / 4000K / 6500K
Specify Wattage:	200W
Specify Finish/Colour:	Silver / Black / Custom
Reflector:	Semi-Specular
Control Option:	Non Dimmable / DALI / 1-10V / Casambi

All product details are subject to change without notice. Final specifications may vary.

