

SDL925 SQUARE SURFACE MOUNT LED DOWNLIGHT

SDL surface mounted LED downlights are a square, compact and stylish fitting for locations that require a surface mounted downlight solution. The fittings have integral LED driver and are protected to IP65 making them suitable for all indoor and outdoor applications.

ELECTRICAL PARAMETERS

Input Voltage:	100-265VAC
Power Consumption:	11W or 23W Options
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	XP-E LED

**MECHANICAL SPECIFICATIONS**


Minimum IK Rating:	IKx
IP Protection Rating:	IP65
Nominal Dimensions:	150 x 150 x 150mm
Construction Material:	Extruded Alloy / Powdercoated
Standard Colour/Finish:	Black / White / Silver
Recommended Ambient Temp:	-20°C - 65°C

**CONFIGURATION OPTIONS**

- 24VDC version available by special request
- Non-standard colours available by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	85-95lm/W
CCT Colour Temperature:	3000K/4000K/6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	24° or 60°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	SDL925
Specify LED CCT:	3000K/4000K/6500K
Specify Beam Angle:	24° or 60°
Specify Finish/Colour:	Black / Silver / White
Input Voltage Option:	85-265VAC
Power Option:	11W / 23W
Control Option:	Non-Dimmable / DALI / Phase Dim



All product details are subject to change without notice. Final specifications may vary.