

**SP10220 SURFACE MOUNT LED SPOTLIGHT**

SP10220 is an architectural surface mounted spotlight for interior applications. Manufactured from quality extruded aluminium and powdercoated for a durable high quality finish. SP10220 is suitable for a wide range of applications such as retail environments, galleries, showrooms, task lighting, hotels and hospitality projects, commercial and residential interior projects.

**ELECTRICAL PARAMETERS**

Input Voltage:	220-240VAC
Power Consumption:	20W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	CREE COB

**MECHANICAL SPECIFICATIONS**

IP Protection Rating:	IP20
Body Dimensions:	79.5x220mm
Overall Height:	230mm
Mounting Base Diameter:	90mm
Construction Material:	Extruded Aluminum
Standard Colour/Finish:	Black / White
Recommended Ambient Temp:	15°C - 45°C

**CONFIGURATION OPTIONS**

- Track mounted version also available
- Non standard colours available by special request
- Integral phase dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	10° / 24° / 38° / 20° / 60°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>SP10220</b>
Specify LED CCT:	<b>3000K / 4000K / 5000K</b>
Specify Beam Angle:	<b>10° / 24° / 38° / 20° / 60°</b>
Specify Finish/Colour:	<b>White / Black / Custom</b>
Mounting:	<b>Surface Mount / Track Mounted</b>
Control Option:	<b>Non-Dimmable / DALI / Phase Dim</b>

All product details are subject to change without notice. Final specifications may vary.

