

SR202 SURFACE MOUNT LED STEPLIGHT

SR202 is a small surface mounted landscape fitting for use in commercial and residential projects. Constructed from die-cast aluminium with a high quality powdercoated finish. SR202 can be wall or ground mounted and is entirely surface mounted making it ideal for installation onto solid block, masonry or concrete surfaces.

ELECTRICAL PARAMETERS

Input Voltage:	12VDC
Power Consumption:	3W
LED Driver Classification:	Remote Constant Voltage
Light Source Classification:	3W SMD

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP67
Mounting Configuration:	Surface Mounted
Overall Dimensions:	68x25mm
Construction Material:	Machined Aluminium
Standard Colour/Finish:	Silver / Black / White
Recommended Ambient Temp:	-15°C - 45°C

CONFIGURATION OPTIONS

- Non standard colours available by special request
- PWM dimmable options available by request
- Remote mounted DALI dimmable LED driver available

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	85lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	100°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	SR202
Specify LED CCT:	3000K / 4000K / 6000K
Installation Configuration:	Surface Mounted
Specify Finish/Colour:	Matt Silver / Black / White
Input Voltage Option:	12VDC
Control Option:	PWM / DALI / Phase Dim

All product details are subject to change without notice. Final specifications may vary.

