

TC4000 WALL MOUNT LED AREA LUMINAIRE

TC4000 is a high quality LED wall luminaire for commercial projects. It is ideally suited for public space lighting, carpark spaces, area lighting, and other commercial landscape lighting applications. TC4000 is constructed from high grade materials with corrosion resistant surface treatment. It features high performance LED light source and specular lens optic.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	45W
LED Driver Classification:	Integral
Light Source Classification:	COB LED



MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Nominal Dimensions:	388x172x97mm
Construction Material:	High Pressure Aluminium
Standard Colour/Finish:	Corrosion Resistant / Matt Grey
Recommended Ambient Temp:	15°C - 45°C

CONFIGURATION OPTIONS

- Pole mounted version also available
- Non standard colours available by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	85lm/w
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	18° / 60°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



CASAMBI

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	TC4000
Specify LED CCT:	3000K / 4000K / 5000K
Specify Beam Angle:	18° / 60°
Specify Finish/Colour:	GREY
Mounting Configuration:	Wall Mount / Pole Mounted
Control Option:	Non Dimmable / DALI / Casambi / DMX



All product details are subject to change without notice. Final specifications may vary.